


# ELGEF® Plus Elektroschweiss-System


PF 2 51 312 001



## Muffe Mit integrierter Rohrfixierung

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Wasser
- 4 mm Steckkontakt
- Wegbegrenzte Schweissanzeige
- Entfernbare Mittenanschlag

| d<br>(mm) | Code               | Gewicht<br>(kg) | d1<br>(mm) | L<br>(mm) | SDR Rohr |
|-----------|--------------------|-----------------|------------|-----------|----------|
| 20        | <b>753 911 606</b> | 0,053           | 31         | 70        | 9-11     |
| 25        | <b>753 911 607</b> | 0,050           | 36         | 70        | 9-11     |
| 32        | <b>753 911 608</b> | 0,071           | 44         | 72        | 9-11     |
| 40        | <b>753 911 609</b> | 0,095           | 54         | 80        | 9-11     |
| 50        | <b>753 911 610</b> | 0,131           | 66         | 88        | 9-11     |
| 63        | <b>753 911 611</b> | 0,194           | 81         | 96        | 9-17.6   |




## Muffe

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Wasser
- 4 mm Steckkontakt
- Wegbegrenzte Schweissanzeige
- bis d160 mit entfernbarem Mittenanschlag

| d<br>(mm) | Code               | PF           | GP | Gewicht<br>(kg) | d1<br>(mm) | L<br>(mm) | SDR Rohr |
|-----------|--------------------|--------------|----|-----------------|------------|-----------|----------|
| 75        | <b>753 911 612</b> | 2 51 312 002 | 12 | 0,282           | 96         | 110       | 9-17.6   |
| 90        | <b>753 911 613</b> | 2 51 312 002 | 10 | 0,406           | 113        | 125       | 9-17.6   |
| 110       | <b>753 911 614</b> | 2 51 312 002 | 5  | 0,692           | 138        | 145       | 9-17.6   |
| 125       | <b>753 911 615</b> | 2 51 312 002 | 5  | 0,718           | 154        | 156       | 9-17.6   |
| 140       | <b>753 911 616</b> | 2 51 312 002 | 5  | 0,945           | 172        | 166       | 9-17.6   |
| 160       | <b>753 911 617</b> | 2 51 312 002 | 6  | 1,362           | 196        | 180       | 9-17.6   |
| 180       | <b>753 911 618</b> | 2 51 312 003 | 5  | 1,747           | 219        | 192       | 9-17.6   |
| 200       | <b>753 911 619</b> | 2 51 312 003 | 4  | 1,866           | 244        | 208       | 9-17.6   |
| 225       | <b>753 911 620</b> | 2 51 312 003 | 3  | 3,329           | 273        | 225       | 9-17.6   |
| 250       | <b>753 911 621</b> | 2 51 312 004 | 2  | 4,678           | 304        | 248       | 9-17.6   |
| 280       | <b>753 911 622</b> | 2 51 312 004 | 2  | 7,500           | 340        | 252       | 9-17.6   |
| 315       | <b>753 911 623</b> | 2 51 312 004 | 2  | 8,142           | 382        | 267       | 9-17.6   |

PF 2 51 312 001



## Muffe Mit integrierter Rohrfixierung

- PE 100 / RC SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Wasser
- 4 mm Steckkontakt
- Wegbegrenzte Schweissanzeige
- Entfernbare Mittenanschlag

| d<br>(mm) | Code               | GP | Gewicht<br>(kg) | d1<br>(mm) | L<br>(mm) | SDR Rohr |
|-----------|--------------------|----|-----------------|------------|-----------|----------|
| 20        | <b>753 911 056</b> | 50 | 0,053           | 31         | 70        | 11       |
| 25        | <b>753 911 057</b> | 50 | 0,050           | 36         | 70        | 11       |
| 32        | <b>753 911 058</b> | 50 | 0,071           | 44         | 72        | 11       |
| 40        | <b>753 911 059</b> | 50 | 0,095           | 54         | 80        | 11       |
| 50        | <b>753 911 060</b> | 30 | 0,131           | 66         | 88        | 11       |
| 63        | <b>753 911 061</b> | 24 | 0,194           | 81         | 96        | 11       |